



NIPPON KAIJI KYOKAI

Certificate

Certificate No.
TA25663E(AL)

OF

APPROVAL

Item : Non-combustible material
Product name : SeaRox SL 620-660
Specifications : See Annex.
Applicant : ROCKWOOL Danmark A/S
Hovedgaden 501, DK-2640 Hedehusene, Denmark
Manufacturers : See Annex.
Testing standard : 2010 FTP Code Annex1 / Part 1
Test reports : See Annex.

THIS IS TO CERTIFY that the above type of products has been approved by Nippon Kaiji Kyokai with type approval No. 04FPA54CM, and that the products of the above type will be accepted for use onboard ships classed with the Society as complying with the relevant requirements of the Society's *Rules for the Survey and Construction of Steel Ships* and those of the *International Convention for the Safety of Life at Sea, 1974*, as amended, conditional upon the manufacturers having a quality control system audited by a competent authority to ensure continuous compliance with the type approval conditions.

This certificate is valid until 29 June 2027.

Issued at Tokyo on 9 June 2025.

NIPPON KAIJI KYOKAI


M. Irisawa

General Manager

Material and Equipment Department

Note: This certificate has been re-issued due to the addition of the manufacturer and amendments of the manufacturer's address.

NOTE: The design, construction and way of installation are subject to the Annex(es). Any significant changes to the product without our approval will result in this certificate becoming null and void.



1. Manufacturers

Rockwool A/S

Industrivej 9-11, Vamdrup, Denmark

Roxul Rockwool Insulation India Pvt. Ltd.

Plot Z/4, Dahej SEZ, Dahej, District Bharuch, Gujarat, India

ROCKWOOL MALAYSIA SDN BHD

175 A & B, Jalan Lingkungan Usaha,

Kawasan Perindustrian Ayer Keroh, Melaka, Malaysia

2. Test Reports

Test laboratory : Danish Institute of Fire and Security Technology
Jernholmen 12, DK-2650 Hvidovre, Denmark

Report numbers : PFB10683A (SL620), PFB10032 (SL640),
PFB10052c(SL660)

Dates of issue : 20 January 2025 (PFB10683A)
20 August 2012 (PFB10032)
19 November 2012 (PFB10052c)

3. Specifications

Density : 100 - 150 kg/m³

Nominal organic content : SeaRox SL 620 : 1.0%
SeaRox SL 640 : 1.4%
SeaRox SL 660 : 1.4%