

ProRox® WM 960^{UK}

ProRox WM 960^{UK} is a lightly bonded heavy duty stone wool mat stitched on galvanised wired mesh with galvanised wire. Stainless steel mesh, stainless steel binding wire (SW) and/or reinforced aluminium foil (ALU) facing are available upon request. The wired mats are produced with an innovative water-repellent binder, known as WR-Tech™, to mitigate the risk of corrosion under insulation (CUI). WR-Tech ensures our stone wool maintains its superior water repellency even at elevated operating temperatures within the CUI range, while preserving its excellent thermal performance in use.



Application

The wired mat is especially suitable for industrial applications such as high-pressure steam pipes, reactors, furnaces, etc. where high demands are made on the temperature resistance of the insulation.

Product properties in accordance with EN 14303:2009+A1:2013



Properties	Performance												Norms
	T (°C)	50	100	150	200	250	300	350	400	500	600	640	
Thermal conductivity	λ (W/mK)	0,040	0,046	0,054	0,063	0,073	0,084	0,098	0,110	0,145	0,180	0,191	EN 12667
Maximum Service Temperature		640 °C											EN 14706
Reaction to fire		Euroclass A1											EN 13501-1
Nominal density		100 kg/m ³											EN 1602
Corrosion resistance		Trace quantity of water leachable chloride ions: ≤ 10 mg/kg											EN 13468
Water Absorption		$\leq 0,2$ kg/m ² $\leq 0,2$ kg/m ² (After 24 hrs. pre-heating at 250°C)											EN 1609 EN ISO 29767
EN 14303 Designation code*		MW EN 14303-T2-ST(+)-640-WS1-CL10											EN 14303

* Thickness class declared under a load of 1000 Pa

Compliance

ProRox WM 960^{UK} fully complies with BS EN 14303 and can be used to satisfy the requirements as set by BS 5422.

As ROCKWOOL has no control over insulation design and workmanship, accessory materials or applications conditions, ROCKWOOL does not warranty the performance or result of any installation containing ROCKWOOL products. ROCKWOOL's overall liability and the remedies available are limited by the general terms and conditions of sale. This warranty in lieu of all other warranties and conditions expressed or implied, including the warranties of merchantability and fitness for a particular purpose. ROCKWOOL Technical Insulation reserves the right to make necessary product changes at any time. Technical specifications are thus stated subject to change.

ROCKWOOL® Technical Insulation, ROCKWOOL®, SeaRox® and ProRox® are registered trademarks of ROCKWOOL A/S and cannot be used without a prior written consent.